

INPUT SPECIFICATION	Options
---------------------	---------

1. Frequency range:	3.4 to 4.8GHz (check model table)	
2. Connector:	N-type	SMA
3. Impedance:	50Ω	
4. Return loss:	≥20dB	

OUTPUT SPECIFICATION	Options
----------------------	---------

5. Frequency range:	70 ± 20MHz or 140 ± 40MHz (check model table)	
6. Connector:	BNC	TNC
7. Impedance:	50Ω	75Ω
8. Return loss:	≥15dB	≥20dB (*)
9. 1dB compression point:	+10dBm	
10. Third order intercept:	+20dBm	

TRANSFER CHARACTERISTICS	Options
--------------------------	---------

11. Gain:	30 to 50dB, adjustable in 0.1dB steps	
12. Gain ripple:	over ±20MHz:	≤1dB p.t.p.
	over input band:	≤3dB p.t.p.
13. Group delay distortion:	over ±5MHz	<2ns
	over ±20MHz	<5ns
14. Gain stability, 0°C to 50°C:	±1dB	
15. Frequency stability, 0°C to 50°C:	10 <sup>-7</sup>	Option 2: 10 <sup>-8</sup>
		Option 3: 3 x 10 <sup>-9</sup>
16. External reference:	10MHz, 0dBm	5MHz, 0dBm
17. Synthesiser step size:	1kHz	
18. Noise figure (full gain):	<17dB	

Spurii
--------

19. Image rejection:	>75dB
20. In-band spurii (at 0dBm output):	<-60dBc

PHASE NOISE
-------------

21. 10Hz:	<-45dBc/Hz
22. 100Hz:	<-70dBc/Hz
23. 1kHz:	<-80dBc/Hz
24. 10kHz:	<-85dBc/Hz
25. 100kHz:	<-95dBc/Hz
26. 1MHz:	<-110dBc/Hz
27. Mains related:	<-60dBc

MISCELLANEOUS
---------------

28. Power supply:	115V/230V ±10% 50/60Hz ±10%, 30VA
29. Mechanical:	1U 19" frame, 400mm deep
30. Temperature:	Operating: 0° to 50°C
	Storage: -40° to 85°C
31. Relative humidity:	Operating: 0 to 90%
	Storage: 0 to 95%
32. Summary alarm:	NO and NC dry relay contacts via rear mounted connector
33. Summary alarm indication:	Front panel LED
34. Remote control:	RS232/RS485 serial interface

(\*) Output compression point and overall gain decrease by 3dB.

### MODEL TABLE

Input Frequency	Output frequency and bandwidth		
	70 ± 20MHz	140 ± 40MHz	70 ± 20MHz, 140 ± 20MHz and ±40MHz
3.625 - 4.2GHz	D550	D555	D570
3.4 - 4.2GHz	D551	D556	D571
4.5 - 4.8GHz	D552	D557	D572
3.4 - 4.2GHz 4.5 - 4.8GHz	D553	D558	D573