

# DBS-Band Compact Klystron High Power Amplifier

The Classic Space-Saving Alternative Solution

## The Compact High Power Amplifier

*DBS-Band CKPA— provides up to 2.4 kW of power in a dual drawer package with power tracker/ power saver*

### Technology Reuse at its Best

Assures high reliability in a compact design based on field proven performance. Features classic klystron technology common to CPI's renowned generations of klystron high power amplifiers.

### Installation Versatility

Racks and stacks two amplifiers into one cabinet in any configuration.

### Useful Displays

Provides a clear, high quality, graphical display with a wide viewing angle and a sharp appearance. Clearly displays all critical functions including a comprehensive event log.

## DBS-Band



### Easy Maintenance, Easy Handling

Offers easy access to all areas of the amplifier with no harness obstructions. Separate RF and Power Supply drawers slide out from a standard rack.

### Worldwide Support

Backed by over three decades of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes sixteen regional factory service centers.

**satcom**  **division**

811 Hansen Way  
P.O. Box 51625, Palo Alto, CA 94303

**tel:** +1 (650) 846-3803  
**fax:** +1 (650) 424-1744

**e-mail:** [satcommarketing@cpil.com](mailto:satcommarketing@cpil.com)  
[www.cpii.com/satcom](http://www.cpii.com/satcom)

DBS-Band

Compact Klystron High Power Amplifier

## SPECIFICATIONS, DBS-Band CKPA

### Electrical

Frequency Ranges	17.3 to 18.1 GHz (to 18.4 GHz optional)
Klystron Power Output	1.7 to 2.4 kW min. (62.3 to 63.8 dBm)
Amplifier Output at Flange <sup>1</sup>	1.4 to 2.0 kW min. (61.46 to 62.01 dBm)
Bandwidth	50 MHz (optional 85 MHz available at 1700 W)
Power Adjustability	0 to -20 dB of output with $\pm 0.1$ dB typical resolution
Gain at Rated Power	75 dB, min.
Gain Stability vs. Time	$\pm 0.25$ dB/24 hr. max. at constant drive and temperature
Gain Stability vs. Temp.	1 dB max. from 20° to 40°C; $\pm 2.5$ dB max from 0° to 50°C (at constant drive)
Gain Slope (at rated power)	0.04 dB/MHz max. over Fo $\pm 18$ MHz
Gain Variation (at rated power)	0.4 dB pk-pk max. over Fo $\pm 18$ MHz
Input VSWR	1.30 max.
Output VSWR	1.35 max.
Load VSWR	2.0:1 max. for full spec. compliance; any value for operation without damage
Residual AM <sup>2</sup>	-50 dBc max., 20 to 400 Hz -60 dBc max., 400 Hz to 2 kHz -80 dBc max., 2 kHz to 500 kHz
AM/PM Conversion (at rated power)	6°/dB max. (7°/dB max. for 2400 W klystron)
Harmonic Output	-80 dBc
Noise and Spurious (at rated gain)	-135 dBW/4 kHz, 10.95 to 12.7 GHz; -65 dBW/4 kHz, in passband -60 dBW/4 kHz, passband with linearizer -55 dBW/4 kHz, passband with BUC; -110 dBW/MHz, 12.7 to 40 GHz (excluding passband)
Phase Noise <sup>2</sup>	Exceeds requirements of INTELSAT Standard IESS-308/309 by -10 dB at -10 dB backoff
Intermodulation	-28 dBc with two equal carriers at total output 7 dB below rated single-carrier output
Group Delay	In any 72 MHz band: 0.10 ns/MHz linear max. 0.02 ns/MHz <sup>2</sup> parabolic max. 2.0 ns pk-pk ripple max.
Primary Power <sup>3</sup>	All ratings are $\pm 10\%$ , 47-63 Hz 3-phase with neutral and ground: 200 VAC w/ neutral 208 VAC 380 to 415 VAC
Power Consumption <sup>4</sup>	11.0 kW max. (12.5 kW for 3.0 kW klystron). Typical values for the following RF output backoffs with respect to rated (power saver on, 2.45 kW klystron): 10.9 kW @ 0 dB (rated) 10.9 kW @ -4 dB 9.0 kW @ -7 dB 7.5 kW @ -10 dB 6.0 kW @ -13 dB

### OPTIONS:

- *Motorized Channel Selector: (<1 second)*
- *Remote Control Panel*
- *Protection Switching*
- *Extended Frequency (17.3-18.4 GHz), available with 1700 watt klystron only*
- *Linearizer*
- *L-Band Block Upconverter (BUC) (Contact factory for typical performance specifications with integrated BUC)*
- *Ethernet Interface*
- *Variable Speed Blower*

### Electrical (continued)

Power Factor	0.95 min.
Inrush Current, peak	180% of normal line current peak max. (first half cycle only)

### Mechanical

RF Input Connection	Type N female
RF Output Connection	WR-62 with grooved flange
RF Power Monitors	Type N female (Type SMA for 18.4 GHz klystron)
Dimension (W x H x D without fans and handles)	
RF Drawer	19 x 21 x 28.75 in. (483 x 533 x 730 mm)
PS Drawer	19 x 8.75 x 24 in. (483 x 223 x 610 mm)
Weight	
RF Drawer	190 lbs w/klystron (86.4 kg)
PS Drawer	95 lbs (43.2 kg) max.
Cooling	Forced air with integral blower and fans; separate klystron collector cooling path
Air Flow Rate, Klystron	300 cfm min., at sea level and 23°C ambient air
External Ducts Backpressure	0.5 inch water gauge total, max.
Klystron Heat Loss <sup>5</sup>	9,500 W typ.
Heat Loss in Room (cabinet less Klystron)	1400 W typ.
Acoustic Noise	68 dBA nominal, measured 3 ft. from front of equipment

### Environmental

Ambient Temperature	-10°C to +50°C operating; -40°C to +80°C non-operating
Relative Humidity	95%, non-condensing
Altitude operating:	10,000 ft. (3000 m) with standard adiabatic temp derating of 2°C/1000 ft. or 6.5°C/km
non-operating:	40,000 ft. (12,000 m)
Shock and Vibration	As normally encountered in satellite earth stations and shipping

<sup>1</sup>Harmonic filter can be removed as an option. Add 0.25 dB to amplifier output for units without harmonic filter. Output VSWR without filter is 1.25:1 max.

<sup>2</sup>Prime power AC line imbalance not to exceed 3%. Excess imbalance may cause an increase in residual RF noise (AM, FM and PM). Phase noise increase is typically 2.5 dB / % imbalance.

<sup>3</sup>AC current harmonic content: less than 20%, primarily fifth and seventh harmonics. Harmonics must be considered when choosing UPS sources.

<sup>4</sup>Lower power consumption can be achieved if power saver (included as standard) is employed when operating below rated output power.

<sup>5</sup>For 2400 W klystron only.



Please check CPI's web site to ensure most current data sheet.

For more detailed information, please refer to the corresponding CPI Technical Description.

Note: Specifications may change without notice as a result of additional data or product refinement.

Please contact CPI before using this information for system design.



Communications & Power Industries

satcom division