HD Satellite Finder

MTR-SATFIND-HD

VIKING SATCOM

Your Trusted Source for Satellite Equipment

- **Quick Satellite ID**
- **Easy to Operate and Highly Sensitive**
- **Update with lyngsat.com**
- **RF Out, HDMI, and Digitial Audio Features Available**

Specifications	
Voltage	AC 100 V/240 V 50 - 60 Hz
Standby Power Consumption	<1 W
SMPS Type	DC 12 V Adapter
LNB In	F Type, Female
RCA	Audio In, Video In
USB	4 Pin Female USB 2.0
Video Resolution	720 x 576 (PAL) 720 x 480 (NTSC)
CPU Frequency	Dual 400 MHz CPU
Flash Memory	8 MB
SDRAM Memory	128 MB
Tuner Type	SHARP BS2S7HZ7306A
Frequency Range	950 - 2150 MHz
Input Impedance	75 Ω
LNB Power and Polarization	13/18 V, 400 mA Max.
Input Level Range	-65 dBm to -25 dBm
LNB Switch Control	22 kHz
DVBS Decoder DVBS	M3501C
DVBS Demod Standard	ETSI EN 302 307
DBVS Demodulation	QPSK/8PSK/16APSK
DBVS Symbol Rate	QPSK:45Ms/s 8PSK:30Ms/s
DVBS Code Rate	QPSK:1/4,1/3,2/5,1/2,3/5,2/3,3/4,4/5,5/6,8/9,9/10 8PSK:3/5,2/3,3/4,5/6,8/9,9/10 16APSK:2/3,3/4,4/5,5/6,8/9,9/10 H8PSK:1/4,1/3
Weight	0.5 kg
Dimensions	10.5 x 16.8 x 4.7 cm

Features

- **Supports DiSEqC 1.0, 1.1, and 1.2**
- **Supports DVB-S/DVB-S2**
- **Simple Media Player Supports MP3, OGG, BMP, JPG, AVI and MPEG Files**
- **Auto Off Screen and Auto Off Meter Extend Battery Life**
- **Can Save Information for Up to 128 Satellites**
- **Detailed Transponder Information for FEC, C/N, MER, workmode, and modulation**

MTR-SATFIND-HD_REV003

Specifications are subject to change without notice

sales@vikingsatcom.com vikingsatcom.com T: 517-629-3000 F: 517-629-2379

704 North Clark Street Albion, Michigan 49224